

*Model 250*

*Clapper Plate Style Exit Alarms*



ALARM LOCK

Door Alarms by Alarm Lock

## Specifications for 250

**Die-Cast Cover Finishes:** US28 Aluminium

**Dimensions:** 18"W x 8 1/2" H x 3 1/4"D (24"W when using extended clapper plate)

**Weight:** 9 lbs.

**Shipping weight:** 10 lbs.

**Mounting Height:** Center of unit should be approximately 38" from the floor

**Special Features:** 250 Models have changeable 2-minute alarm cutoff or manual reset

**Standard Features:** Non-handed surface installations on single or double doors. Audible low battery warning and cam for exterior key control. Low activation pressure. Includes door warning sign.

**Power:** 9VDC Alkaline Battery (use optional "AC9" or "PP100" for AC power with battery backup). Current (Standby) – 7 Micro Amps typical. Battery Life – one year standby typical; 200 Alarm sequences typical; constant alarm 7 hours typical

**Lock Bolt:** 1" throw – Heavy die cast zinc alloy with reinforced steel inserts


**Sound Pressure Level:** 95 db Dual Piezo Horn (measured at 10')

**Operating Temperature:** 20°F to 135°F (-7°C to 57°C)

## Features for 250

- Deadbolt and deadlatch meet relatching requirements
- Blaring 95 db dual tone Piezo alarm
- Selectable 2-minute alarm or constant alarm
- 9V battery powered and audible low battery warning
- Non-handed surface installations on single or double doors
- Meet or exceed UL, CFM, ADA, NYC housing requirements
- 250 Models have changeable 2-minute alarm cutoff or manual reset

Pairs of Doors



If two exit devices are not required, use one lock with a Model 735 Double Door Keeper – plus one Model 44 Double Door Holder on the inactive door (or vertical rod).

Pairs of Doors with Center Mullions



Pairs of this style should be treated as two single exit doors. Use two locks for maximum safety and security.



**ALARM LOCK SYSTEMS, Inc.**  
**A NAPCO Security Group Company**

### Regional Representative Office

5/F, 677 King's Road, Quarry Bay, Hong Kong  
 Phone: 2880-0207 • Fax: 2856-1184  
[www.sprintlocks.com/alarmlock](http://www.sprintlocks.com/alarmlock)